



### Features

- Solid Aluminum Die-casting chassis
- Variety of LCD panel type selections
- Front bezel IP65
- VGA/DVI input
- 9~36V DC wide range power input



### Dimension



### Specifications

#### LCD

Display Type	15" TFT-LCD
Max. Resolution	1024x768
Max. Color	16M
Luminance (cd/m <sup>2</sup> )	330
View Angle	H:170° / V:170°
Backlight Lifetime	50,000 hrs
Contrast	800:1

#### System

OSD Control	5 keys
Membrane	
External I/O Port	1 x VGA, 1 x DVI USB interface for touch RS-232 for resistive touch 1x tack switch for VGA/DVI switching 1x Line in by phone jack for option 3 pins terminal block
Power Input	9~36V DC
Touch Screen	115P:Projected Capacitive Touch 115:Resistive Touch Window
Light Transmission	ARCDIS-115P:90% / ARCDIS-115:80%
Interface	ARCDIS-115P:USB ARCDIS-115:USB/RS-232
Power Consumption	Max:11W

#### Mechanical

Construction	Aluminum Die-casting chassis
IP Rating	IP65 front panel, other sides IPx0
Mounting	Panel mounting, VESA 100 x 100
Dimension	410 x 310 x 53
Net Weight	TBD

#### Environmental

Operating Temperature	0~50 °C
Storage Temperature	-20~60 °C
Storage Humidity	10 to 90% @ 40°C, non- condensing, without touch screen
Certificate	CE/FCC Class A

