

Industrial Display Monitor

15" Color TFT Industrial Display Monitor

ADP-1150

Features

- 15" TFT XGA LCD
- 1024(H)x768(V), 400 cd/m²
- Front panel NEMA 4/IP 65 rating
- Wall-mount screw holes
- Resistive touch screen (optional)
- Optional DVI, Video or S-Video input
- Optional stainless steel front bezel
- Support wide-ranging resolutions from 640x480 to up to 1600 x 1200 with auto phase and auto position

Display Specifications

Display	15" Color Active TFT Flat Panel Display
Luminance	400 cd/m ²
Viewing Angle	140/125 (H/V)
Resolutions	1024 x 768 (native mode), 16.2M colors
Backlight	50,000hrs
Touch Screen	Resistive Antiglare
OSD Controls/Indicators	Automatic Screen, Setup (OSD), Brightness, Contrast, Horizontal/Vertical Position, Image Lock, Color Balance, Video Information, Power On and Sync Detection
Power Input	AC 100~240V

Mechanical Specifications

Construction	Steel chassis & front bezel
Dimensions	410(W)x310(H)x69(D)mm
Mounting	Panel Mount / Rack Mount (optional)

Environment Specifications

Operating Temperature	0~50°C (32~122°F)
Storage Temperature	-20~60°C (-4~140°F)
Relative Humidity	10~90% @40°C Non-condensing, without touch screen
Vibration	1G peak, 5~500 Hz (Random)
Shock	15G peak acceleration (11 msec. duration)
Ratings	NEMA 4/IP 65
Certifications	CE and FCC class A

Dimensions

