

Industrial Display Monitor

19" SXGA Industrial Display Monitor

ADP-1191

Features

- 19" SXGA Color TFT LCD
- 1280(H)x1024(V), 250 cd/m²
- Front Panel NEMA 4/IP 65 rating
- Support Panel / VESA 75 Mount
- Resistive touch screen (optional)
- Optional DVI, Video and S-Video input
- Backlight Lifetime of 50,000 Hours
- Support wide-ranging resolutions from 640x480 to up to 1600 x 1200 with auto phase and auto position

Display Specifications

Display	19" Color Active TFT Flat Panel Display
Luminance	250 cd/m ²
Viewing Angle	140/140(H/V)
Resolutions	1280 x 1024 (native mode), 256K colors
Backlight	50,000hrs
Touch Screen	Resistive Antiglare
OSD Controls/Indicators	Automatic Screen, Setup (OSD), Brightness, Contrast, Horizontal/Vertical Position, Image Lock, Color Balance, Video Information, Power On and Sync Detection
Power Input	AC 100~240V

Mechanical Specifications

Construction	Steel chassis & Aluminum front bezel
Dimensions	460(W)x400(H)x68.5(D)mm
Mounting	Panel / VESA 75 mount

Environment Specifications

Operating Temperature	0~45°C (32~113°F)
Storage Temperature	-20~60°C (-4~140°F)
Relative Humidity	10~95% @40°C Non-condensing, without touch screen
Vibration	1G peak, 10~150 Hz (Random)
Shock	15G peak acceleration (11 msec. duration)
Ratings	NEMA 4/IP 65
Certifications	CE and FCC class A

Dimensions

