

# Industrial Display Monitor

## 19" SXGA Industrial Display Monitor

**ADP-1194**



### Features

- 19" SXGA Color TFT LCD
- 1280(H)x1024(V), 300 cd/m<sup>2</sup>
- NEMA 4/IP 65 compliant front bezel
- Support Panel / VESA 75 Mount
- Resistive touch screen (optional)
- Optional DVI, Video and S-Video input
- Optional Aluminum front bezel
- Support wide-ranging resolutions from 640x480 to up to 1600 x 1200 with auto phase and auto position



### Display Specifications

Display	19" Color Active TFT Flat Panel Display
Luminance	300 cd/m <sup>2</sup>
Viewing Angle	160/160(H/V)
Resolutions	1280 x 1024 ( native mode), 16.7M colors
Backlight Lifetime	50,000hrs
Touch Screen	Analog resistive (optional)
OSD Control	On the front side
I/O Connectors	1xAC power input, 1xVGA, optional:DVI,S-Video,RCA, touch (RS-232 or USB)
Power Input	AC 100~240V, optional DC 11~28V

### Mechanical Specifications

Construction	Steel front bezel & Steel chassis
Dimensions	467(W)x379(H)x64.7(D)mm
Mounting	Panel / VESA 75 mount

### Environment Specifications

Operating Temperature	0~50°C (32~122°F)
Storage Temperature	-20~60°C (-4~140°F)
Relative Humidity	10~95% @40°C Non-condensing, without touch screen
Vibration	1G peak, 10~150 Hz (Random)
Shock	15G peak acceleration (11 msec. duration)
Rating	NEMA 4/IP 65 compliant front bezel
Certificate	Meet CE / FCC Class A

### Optional Specifications

Aluminum front bezel & steel chassis

### Dimensions

