

Industrial Panel PC

APC-3212/3512/
3712/3912

12.1"/15"/17"/19" Fanless TFT LCD Panel PC



Features

- Fanless design Celeron M 1.5GHz up to Pentium M 1.8GHz CPU
- NEMA 4/IP 65 compliant front bezel
- Resistive touch screen (optional)
- 2 x PCI expansion slots
- 2 x COM ports and 4 x USB 2.0 ports
- Space for one 2.5" HDD and slim CD-ROM
- Optional stainless steel front bezel (3512/3712/3912)
- Support Panel mount
- DC 11~28V wide-range power input

System Specifications

Specs	Models	APC-3212	APC-3512	APC-3712	APC-3912
CPU		Intel Celeron M 1.5GHz up to Pentium M 1.8GHz			
DRAM		up to 1GB DDR SDRAM			
Storage		Space for 1x 2.5" HDD and 1x slim CD-ROM			
I/O Ports		2 x COM ports, 4 x USB 2.0, 1 x PS/2 keyboard & mouse, 1 x LAN 1 x Audio Mic, Line-in, Line-out, 1 x parallel port, 1 x VGA, 1 x DVI			
Expansion		2 x PCI slots			
Fanless / Fan		Fanless			
Touch screen		Analog resistive (optional)			
Display Specifications					
LCD		12.1" SVGA	15" XGA	17" SXGA	19" SXGA
Resolution		800x600	1024x768	1280x1024	
Luminance (cd/m ²)		300		300	
Dimension		390(W)x265(H)x127(D)mm	410(W)x310(H)x127(D)mm	457(W)x355(H)x133(D)mm	484(W)x400(H)x139.3(D)mm
Backlight Lifetime		50,000hrs			
Mechanical Specifications					
Construction		Heavy-duty steel chassis, Stainless Steel front bezel (optional for 15"/17"/19")			
Power input		DC 11~28V			
Operating Temperature		0~50° C			
Storage Temperature		0~60° C			
Certifications		CE and FCC class A			
Rating		NEMA 4/IP 65			
Mounting		Panel mount			

Dimensions

