

Industrial Panel PC

12.1"/15"/17"/19" TFT LCD Core 2 Duo Panel PC

APC-3215/3515/
3715/3915



Features

- Support Intel Core 2 Duo, 1GHz up to 2.0GHz processor
- NEMA 4 / IP 65 compliant front bezel
- Resistive touch screen (optional)
- 2 x DDR2 DIMM socket, up to 4GB
- 2 x PCI expansion slots
- Space for one 2.5" HDD and one slim CD-ROM / DVD Combo
- Optional stainless steel front bezel
- Support Panel mount
- AC 100~240V power input, optional DC 16~36V with 19V adapter

System Specifications

Specs	Models	APC-3215	APC-3515	APC-3715	APC-3915
CPU		Intel Core 2 Duo, 1GHz up to 2.0GHz			
DRAM		2 x 240-PIN Dual channel DDRII 533/667MHz up to 4GB			
Storage		Space for 1x 2.5" HDD and 1 x slim CD-ROM / DVD Combo			
I/O Ports		3 x COM (RS-232), 1 x PS/2 keyboard, 1 x PS/2 mouse, 1 x VGA, 2 x LAN (GbE), 1 x Line-out, Mic, 4 x USB 2.0,			
Expansion		2 x PCI slots			
Fanless / Fan		Fan			
Touch screen		Analog Resistive (optional)			
Display Specifications					
LCD		12.1" SVGA	15" XGA	17" SXGA	19" SXGA
Resolution		800x600	1024x768	1280x1024	
Luminance (cd/m ²)		300	450	300	
Dimension		390(W)x265(H)x122(D)mm	410(W)x310(H)x122(D)mm	457(W)x355(H)x128(D)mm	484(W)x400(H)x129(D)mm
Backlight Lifetime		50,000hrs			
Mechanical Specifications					
Construction		Heavy-duty steel chassis, Stainless Steel front bezel (optional)			
Power input		AC 100~240V, optional DC 16~36V with 19V adapter			
Operating Temperature		0~50° C			
Storage Temperature		-20~60° C			
Rating		NEMA 4/IP 65 compliant front bezel			
Certificate		Meet CE / FCC Class A			
Mounting		Panel mount			

Dimensions

