

Industrial Panel PC

17" Slim / All in One Panel PC with 1 x PCI Slot

APC-3717



Features

- 17" Slim / All in One Panel PC
- Support Intel Socket P Core 2 Duo Processor, up to T7250 Processor (2M Cache, 2.00 GHz, 800 MHz FSB)
- 17" High brightness (300cd/m²) TFT LCD with resolution of 1280x1024
- Support 1 x PCIe Mini Card socket onboard
- Support 1 x PCI slot
- Space for 1 x 2.5 SATA HDD and 1 x internal CF slot
- Sealed resistive touch screen (optional)
- Support panel mount and VESA 75 mount
- DC 16~32V power input

System Specifications

| | |
|---------------|--|
| CPU | Intel Socket P Core 2 Duo Processor, up to T7250 Processor (2M Cache, 2.00 GHz, 800 MHz FSB) |
| DRAM | 2 x 240-PIN Dual channel DDRII 533/667MHz up to 4GB |
| Storage | Space for 1x 2.5" SATA HDD, 1 x Internal CF slot |
| I/O Ports | 3 x COM (RS-232), 1 x PS/2 keyboard, 1 x PS/2 mouse, 1 x VGA , 2 x LAN (GbE), 1 x Audio Mic, Line-out, 4 x USB 2.0 |
| Expansion | 1 x PCI slot |
| Fanless / Fan | Fanless |
| Touch screen | Analog resistive (optional) |
| OS Support | Microsoft Windows XP Pro, XP Embedded |

Display Specifications

| | |
|--------------------------------|-------------------------|
| LCD | 17" SXGA |
| Resolution | 1280x1024 |
| Luminance (cd/m ²) | 300 |
| Dimension | 439(W)x348(H)x93.3(D)mm |
| Backlight Lifetime | 50,000hrs |

Mechanical Specifications

| | |
|-----------------------|--|
| Construction | Heavy-duty steel chassis (Black color), Stainless steel front bezel (optional) |
| Power Supply | DC 16~32V |
| Operating Temperature | 0~50 °C (32~122°F) |
| Storage Temperature | -20~60 °C (-4~140°F) |
| Relative Humidity | 10~90% @40 °C, Non-condensing |
| Vibration | 5~17Hz, 0.1" double amplitude peak to peak, 17-640Hz, 1.5G acceleration peak to peak |
| Shock | 10G acceleration peak to peak (11ms) |
| Rating | NEMA 4/IP 65 compliant front bezel |
| Certificate | Meet CE / FCC Class A |
| Mounting | Panel / VESA 75mount |
| Weight (net) | 12.8kgs |

Dimensions

