

Industrial Panel PC

19" TFT LCD Core 2 Duo Industrial Panel PC

APC-3915



Features

- Support Intel Socket P Core 2 Duo / Core Duo / Celeron M CPU
- 19" High Brightness (300 cd/m²) TFT LCD with resolution of 1280x1024
- NEMA 4 / IP 65 compliant front bezel
- Sealed resistive touch screen (optional)
- 2 x DDR2 DIMM socket, up to 4GB
- 2 x PCI expansion slots
- Space for one 2.5" HDD and one slim CD-ROM / DVD Combo
- Optional stainless steel front bezel
- Support Panel mount
- AC 100~240V power input, optional DC 16~36V with 19V adapter

System Specifications

| | |
|---------------|---|
| CPU | Intel Socket P Core 2 Duo / Core Duo / Celeron M CPU |
| DRAM | 2 x 240-PIN Dual channel DDRII 533/667MHz up to 4GB |
| Storage | Space for 1x 2.5" HDD and 1 x slim CD-ROM / DVD Combo |
| I/O Ports | 3 x COM (RS-232), 1 x PS/2 keyboard, 1 x PS/2 mouse, 1 x VGA, 2 x LAN (GbE), 4 x USB 2.0, 1 x Line-out, Mic |
| Expansion | 2 x PCI slots |
| Fanless / Fan | Fan |
| Touch screen | Analog resistive (optional) |
| OS Support | Microsoft Windows XP Pro, XP Embedded |

Display Specifications

| | |
|--------------------------------|------------------------|
| LCD | 19" SXGA |
| Resolution | 1280x1024 |
| Luminance (cd/m ²) | 300 |
| Dimension | 484(W)x400(H)x129(D)mm |
| Backlight Lifetime | 50,000hrs |

Mechanical Specifications

| | |
|-----------------------|--|
| Construction | Heavy-duty steel chassis, Stainless steel front bezel (optional) |
| Power Supply | AC 100~240V, optional DC 16~36V with 19V adapter |
| Operating Temperature | 0~50 °C |
| Storage Temperature | -20~60 °C |
| Relative Humidity | 10~90% @40 °C, Non-condensing |
| Vibration | 5~17Hz, 0.1" double amplitude peak to peak, 17-640Hz, 1.5G acceleration peak to peak |
| Shock | 10G acceleration peak to peak (11ms) |
| Rating | NEMA 4/IP 65 compliant front bezel |
| Certificate | Meet CE / FCC Class A |
| Mounting | Panel mount |

Dimensions

